

Vtoková mříž v litinovém rámu

D400 - těžké dopravní zatížení

Standard



Kód	KML29
Materiál	Litina
Hmotnost	108 kg
Norma	DIN1229, EN124-2
Balení	16 ks/pal

Mříž 500x500mm pro uliční vpusti.

VÍKO:

- | Mříž rovná mezi žebry 16 mm
- | Rozebíratelné spojení mříže s rámem
- | Úzkoštěrbinová mříž

RÁM:

- | Litinový rám s osazením pro lapač
- | výška rámu 160 mm

OSTATNÍ:

- | Osadit na vyrovnávací prstenec 10A.
- | Mezi rámem a vrchním dílem vpusti musí být alespoň 20mm vysoké maltové spojení s pevností min.45MPa

Warning: file_exists(): open_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4768.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**

Warning: file_exists(): open_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4768.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**



ODVOD
DEŠŤOVÝCH VOD

