

Šachtový poklop hranatý bez odvětrání v litinovém rámu s patkou

E600 - plochy vystavené vysokému zatížení těžkou technikou

Standard



Kód	KQ99EL05CS
Materiál	Litina
Hmotnost	178 kg
Norma	EN124-2
Balení	8 ks/pal
Třída zatížení	Vysoké dopravní zatížení

čtvercový poklop, bez pantu, KASI PUR tlumící vložka, bez pružinového zajištění víka v rámu, se zajištěním

VÍKO:

- | Litinové bez odvětrání s tichým designem.
- | Možnost vlastního motivu / loga

RÁM:

- | Litinový rám s patkou v.100mm, bez osazení pro lapač
- | Integrovaná PUR tlumící vložka s vysokou odolností

OSTATNÍ:

- | Poklop je dodáván s černou povrchovou úpravou

Warning: file_exists(): open_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4935.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**

Warning: file_exists(): open_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4935.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-

dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**



**ZÁKAZNICKÁ
ŘEŠENÍ**

