

Spodní díl uliční vpusti DN450 s vývodem

Betonový díl s vývodem DN200



Kód	BU1D
Materiál	Beton
Hmotnost	79 kg
Norma	DIN1917
Balení	12 ks/pal

Díl uliční vpusti 1D, spodní díl s vývodem DN200, přechodka na PVC KG, výška 380mm, dle ČSN EN 1917, pevnost betonu 40 MPa, chemická odolnost XF4
TBV-Q 450/330/1d

OSTATNÍ:

- Díly pro sestavy uličních vpustí DN450.
- síla stěny 45 mm
- možnost dodání i s přechodkou pro PRAGMA ID

Warning: file_exists(): open_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4848.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in /var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php on line 272

Warning: file_exists(): open_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4848.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in /var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php on line 272



ODVOD
DEŠŤOVÝCH VOD

