

Skruž uliční vpusti DN450 s vývodem

Středový díl uliční vpusti DN450



Kód	BU3S15P
Materiál	Beton
Hmotnost	157 kg
Norma	DIN1917
Balení	2 ks/pal

Díl uliční vpusti 3Z, střední díl s vývodem DN150, protizápachová uzávěra, přechodka PVC KG, výška 550mm, dle ČSN EN 1917, pevnost betonu 40 MPa, chemická odolnost XF4 TBV-Q 450/550/3z

OSTATNÍ:

| síla stěny 45 mm

Warning: file_exists(): open_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4863.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**

Warning: file_exists(): open_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4863.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**



ODVOD
DEŠŤOVÝCH VOD

